



Pin	Signal	Description
1	RXD	RS-232 Receive data
2	TXD	RS-232 Transmit data
3	VCC	+5 Volt or DTR
4	GND	Ground

# OP-330

## Optical probe with RS-232 output signal

### Overview

OP-330 is an IEC62056-21 optical head with RS232 (DIN-5) output that communicates with all types of metering devices that are compliant with IEC62056-21 standard via infrared. This device can be used for onsite reading and configuring of all types of meters or other devices that are compatible with IEC62056-21 standard.

### Mechanical description

Connector	DIN 5 Pin male
Infrared filter against external light influences	
Dimensions (Ø x H)	approx. 32 x 26 mm
Magnetical holding force	> 15 N
Casing material	ABS
Cable	Length 2 m, Ø 4,5 mm, four-wire cable LAPP GERMANY
Weight	approx. 110 gr

### Electronical Description

Standard	IEC 62056-21 (IEC 1107)
Power supply	no power supply required. Supplied from RS-232 interface
Consumed current	approx. 5 mA (Transmitting operation)
Signal level	Compatible with EIA-232 (RS-232)
Data baud rate	from 300 to 19200 bit/s
Wavelength	880nm
Echo filter	yes



**GERMAN METERING GmbH**

Reutenweg 65, 60323 Frankfurt am Main, Germany  
 Telephone: +49 (0)69 / 77062206, Fax: +49 (0)69 / 77062226  
 www.german-metering.com

GM-0263-2006-PB-00

